

<b>Linux From Scratch - Version 12.1-systemd</b>		
<b>Chapter 7. Entering Chroot and Building Additional Temporary Tools</b>		
	/	
가		

# 7.4. Chroot 가

```

root 가 . 가 chroot

```

```

chroot "$LFS" /usr/bin/env -i \
HOME=/root \
TERM="$TERM" \
PS1='(lfs chroot) \u:\w\$ ' \
PATH=/usr/bin:/usr/sbin \
MAKEFLAGS="-j$(nproc)" \
TESTSUITEFLAGS="-j$(nproc)" \
/bin/bash --login

```

```


가
$(nproc) . 8 ( Autoconf, Libtool, Tar)
MAKEFLAGS TESTSUITEFLAGS

env -i chroot 가 HOME, TERM, PS1
PATH . TERM=$TERM TERM chroot
CXXFLAGS 가 vim . CFLAGS

chroot (/) $LFS Bash LFS 가
/tools/bin

bash I have no name! 가 ! /etc/passwd

```



가 " chroot 7.3.1 "/dev " 7.3.2 "

가 chroot

From:  
<https://www.gamu.kr/dokuwiki/> -

Permanent link:  
[https://www.gamu.kr/dokuwiki/linuxfromscratch/12.1/061-entering\\_the\\_chroot\\_environment?rev=1718446469](https://www.gamu.kr/dokuwiki/linuxfromscratch/12.1/061-entering_the_chroot_environment?rev=1718446469)

Last update: **2024/06/15 10:14**

