

Linux From Scratch - Version 12.1-systemd		
Chapter 9. System Configuration		
	/	
/etc/inputrc	Systemd	

9.10. Systemd

9.10.1.

etc/systemd/system.conf

systemd

가
system.conf(5)

systemd-

9.10.2.

systemd

가

```
mkdir -pv /etc/systemd/system/getty@tty1.service.d
```

```
cat > /etc/systemd/system/getty@tty1.service.d/noclear.conf << EOF
[Service]
TTYVTDisallocate=no
EOF
```

```
journalctl -b
```

9.10.3. tmpfs /tmp

```
/tmp tmpfs
```

```
ln -sfv /dev/null /etc/systemd/system/tmp.mount
```

```
/tmp
```

```
/etc/fstab
```



```
/tmp
```

```
(/)
```

9.10.4.

가 가 .

- systemd-tmpfiles-clean.service
- systemd-tmpfiles-setup-dev.service
- systemd-tmpfiles-setup.service

/usr/lib/tmpfiles.d/*.conf .
/etc/tmpfiles.d . /etc/tmpfiles.d /usr/lib/tmpfiles.d
가 tmpfiles.d(5)

usr/lib/tmpfiles.d/*.conf /tmp
/usr/lib/tmpfiles.d/tmp.conf

```
q /tmp 1777 root root 10d
```

q , btrfs
가 , d()
가
/etc/tmpfiles.d

```
mkdir -p /etc/tmpfiles.d  
cp /usr/lib/tmpfiles.d/tmp.conf /etc/tmpfiles.d
```

9.10.5.

etc/systemd/system

```
mkdir -pv /etc/systemd/system/foobar.service.d  
cat > /etc/systemd/system/foobar.service.d/foobar.conf << EOF  
[Service]  
Restart=always  
RestartSec=30  
EOF
```

[systemd.unit\(5\)](#) **systemctl**
daemon-reload **systemctl restart foobar**

9.10.6.

```

SysVinit      BSD      init      systemd
(            )      . systemctl      ,
,            .      가      .

```

- **systemctl list-units -t <service> [-all]:**
- **systemctl list-units -t <target> [-all]:**
- **systemctl show -p Wants <multi-user.target>:**
 . Target SysVinit .
- **systemctl status <servicename.service>:**
 가 (:.socket (inetd/xinetd
)) .

9.10.7. Systemd

```

systemd      syslog daemon      systemd-journald(
)            가
. systemd-journald      .
.            journalctl      가
.

```

- **journalctl -r:**
- **journalctl -u UNIT:** UNIT
- **journalctl -b[=ID] -r:** (ID)
- **journalctl -f:** tail -f()

9.10.8.

```

가
systemd-coredump
/var/lib/systemd/coredump
coredumpctl 가            가

```

- **coredumpctl -r:**
 - **coredumpctl -1 info:**
 - **coredumpctl -1 debug:** [GDB](#) .
- ```

/etc/systemd/coredump.conf.d 가

```

```
mkdir -pv /etc/systemd/coredump.conf.d
```

```

cat > /etc/systemd/coredump.conf.d/maxuse.conf << EOF
[CoreDump]
MaxUse=5G

```

EOF

[systemd-coredump\(8\)](https://man.archlinux.org/man/coredumpctl.1), <https://man.archlinux.org/man/coredumpctl.1>  
[coredump.conf.d\(5\)](#)

9.10.9.

```
systemd-230 nohup 가 daemon ()
setsid() 가
 (: tmux)
 가
•
loginctl enable-linger
 user
 systemd-run
 systemd-run -scope -user /usr/bin/screen
 user@.service가
 nohup daemon ()
•
 . etc/systemd/logind.conf
 KillUserProcesses=no
 가
•
 : systemd meson -Ddefault-kill-user-processes=false
 가
 systemd가
```

From: <https://www.gamu.kr/dokuwiki/> -

Permanent link: [https://www.gamu.kr/dokuwiki/linuxfromscratch/12.1/163-systemd\\_usage\\_and\\_configuration?rev=1718457846](https://www.gamu.kr/dokuwiki/linuxfromscratch/12.1/163-systemd_usage_and_configuration?rev=1718457846)

Last update: 2024/06/15 13:24

