

Linux From Scratch - Version 12.1-systemd		
Chapter 11. The End		
	/	
가		

11.5. LFS

11.5.1.

LFS가 가 ? 가

가 . Apache HTTP 가 MariaDB

가 . USB

가 . LXDE,

XFCE, KDE Gnome Firefox , Thunderbird

LibreOffice 가

가 가

가 BLFS wireless_tools

dhcpd

11.5.2. LFS

LFS 가 가 가 .

11.5.2.1. LFS 가

가 / wget

가 가

```
cat > ~/mount-virt.sh << "EOF"
#!/bin/bash
```

```
function mountbind
{
    if ! mountpoint $LFS/$1 >/dev/null; then
        $SUDO mount --bind /$1 $LFS/$1
        echo $LFS/$1 mounted
    else
        echo $LFS/$1 already mounted
    fi
}

function mounttype
{
    if ! mountpoint $LFS/$1 >/dev/null; then
        $SUDO mount -t $2 $3 $4 $5 $LFS/$1
        echo $LFS/$1 mounted
    else
        echo $LFS/$1 already mounted
    fi
}

if [ $EUID -ne 0 ]; then
    SUDO=sudo
else
    SUDO=""
fi

if [ x$LFS == x ]; then
    echo "LFS not set"
    exit 1
fi

mountbind dev
mounttype dev/pts devpts devpts -o gid=5,mode=620
mounttype proc proc proc
mounttype sys sysfs sysfs
mounttype run tmpfs run
if [ -h $LFS/dev/shm ]; then
    install -v -d -m 1777 $LFS$(realpath /dev/shm)
else
    mounttype dev/shm tmpfs tmpfs -o nosuid,nodev
fi

#mountbind usr/src
#mountbind boot
#mountbind home
EOF
```

LFS/BLFS

() bash ~/mount-virt.sh
sudo가

() /sources BLFS (: ~/sources) LFS (: /usr/src) 1)

가
~/bashrc

```
alias lfs='sudo /usr/sbin/chroot /mnt/lfs /usr/bin/env -i HOME=/root
TERM="$TERM" PS1="\u:\w\\\$ " PATH=/bin:/usr/bin:/sbin:/usr/sbin /bin/bash
-login'
```

alias

11.5.2.2. ssh

LFS () sshd
가
가 LFS

scp LFS libtasn1, p11-kit, make-ca wget LFS
scp LFS

11.5.2.3. LFS

chroot libtasn1, p11-kit, make-ca, wget, gpm link(lynx)
LFS 6 가
Alt+Fx (Fx F1 F6).
Alt+← Alt+→
가 lynx
bash



가
Ctrl+Alt+Fx
F1 F7

X Window
가
X

Ctrl+Alt+Fx
Fx

1)

`mount -bind <target> <mountpoint>`

가

From:

<https://www.gamu.kr/dokuwiki/> -

Permanent link:

https://www.gamu.kr/dokuwiki/linuxfromscratch/12.1/172-getting_started_after_ifs?rev=1718469549

Last update: **2024/06/15 16:39**

