

1. \$LFS/sources

```
alias dirfind="find -mindepth 1 -maxdepth 1 -type d | sed 's@^./@@'"
dirfind | wc -l    ##
rm -rf $(dirfind) ##
```

2. SBU

```
##          +          가
alias lfslog='tee ~/lfs-log/${case $(basename $(pwd)) in build) echo
$(basename $(dirname $(pwd))); ;; *) echo $(basename $(pwd)); ;;
esac}.${date "+%Y%m%d_%H%M%S"}.log'
time { ./configure ... && make && make install; } | lfslog
```

3.

```
<a href=""></a> ##
<a target="_blank" rel="noopener noreferrer" href=""></a> ##
```

```
./configure --prefix=/usr \
--bindir=/usr/bin \
--localstatedir=/var \
--disable-logger \
--disable-whois \
--disable-rcp \
--disable-rexec \
--disable-rlogin \
--disable-rsh \
--disable-servers
```

Same Command

```
./configure --prefix=/usr --bindir=/usr/bin --localstatedir=/var \
--disable-{logger,whois,r{cp,exec,login,sh},servers}
```

tar

```
tar -cf - . | tar -xvf - -C /target_directory
```

find example

```
find /media/d/ -type f -size +50M -and ! -name "*deb" -and ! -name "*vmdk"
```

From:

<https://www.gamu.kr/dokuwiki/> -

Permanent link:

<https://www.gamu.kr/dokuwiki/linuxfromscratch/shellcommand?rev=1712546666>

Last update: **2024/04/08 03:24**

