

```
if [ -d ~/.bin ]; then
    new_root_bin_path=~/.bin
    case ":$PATH:" in
        *:$new_root_bin_path:*) ;; # already there
        *) PATH="$new_root_bin_path:$PATH";; # or
    esac
    PATH="$PATH:$new_entry"
fi
```

```
<a href=""></a> ##
<a target="_blank" rel="noopener noreferrer" href=""></a> ##
```

```
./configure --prefix=/usr \
            --bindir=/usr/bin \
            --localstatedir=/var \
            --disable-logger \
            --disable-whois \
            --disable-rpc \
            --disable-rexec \
            --disable-rlogin \
            --disable-rsh \
            --disable-servers
```

## Same Command

```
./configure --prefix=/usr --bindir=/usr/bin --localstatedir=/var \
            --disable-{logger,whois,r{cp,exec,login,sh},servers}
```

```
## history ls, cd
export HISTIGNORE="ls*:cd*"
```

```
$( [ $(uname -m) = x86_64 ] && echo USE_64=1 ) \
$( [ -f /usr/include/sqlite3.h ] && echo NSS_USE_SYSTEM_SQLITE=1)
```

From:  
<https://www.gamu.kr/dokuwiki/> -

Permanent link:  
<https://www.gamu.kr/dokuwiki/misc?rev=1714234605>

Last update: **2024/04/27 16:16**



