

```
echo "sources/automake-1.16.5.tar.xz" | sed 's/.tar.*$//'
```

```
if [ -d ~/.bin ]; then
    new_root_bin_path=~/.bin
    case ":$PATH:" in
        *:$new_root_bin_path:*) ;; # already there
        *) PATH="$new_root_bin_path:$PATH";; # or
PATH="$PATH:$new_entry"
    esac
fi
```

```
<a href=""></a> ##
```

```
<a target="_blank" rel="noopener noreferrer" href=""></a> ##
```

```
./configure --prefix=/usr \
--bindir=/usr/bin \
--localstatedir=/var \
--disable-logger \
--disable-whois \
--disable-rpc \
--disable-rexec \
--disable-rlogin \
--disable-rsh \
--disable-servers
```

```
## Same Command
```

```
./configure --prefix=/usr --bindir=/usr/bin --localstatedir=/var \
--disable-{logger,whois,r{cp,exec,login,sh},servers}
```

```
## history ls, cd
export HISTIGNORE="ls*:cd*"
```

```
$([ $(uname -m) = x86_64 ] && echo USE_64=1) \
$([ -f /usr/include/sqlite3.h ] && echo NSS_USE_SYSTEM_SQLITE=1)
```

From:

<https://www.gamu.kr/dokuwiki/> -

Permanent link:

<https://www.gamu.kr/dokuwiki/misc?rev=1714258391>

Last update: **2024/04/27 22:53**

